

SICON

Control and evaluation unit with touch screen and data logger



Applications

- Control unit in combination with SGRIST photometers

Advantages

- Intuitive operability
- Touchscreen with colour display
- Optional display of measured values, graphics, status and alarm messages
- An internal data memory allows the display of measurement data over the last 32 days
- A password protects against unauthorised access
- Extensive communication options inclusive integrated web server

- Optional variant: SICON M enables the operation of several devices and up to eight measuring channels

Industries

- Water
- Beverage and food industry
- Industrial Processes
- Traffic and environment

Innovationen with true customer benefits



Intuitive operability

- Control of the unit recalibration
- Warnings & error messages in text form
- Striking colour background for warning and error messages
- Callable memory for calibration procedures and error messages
- Up to four readings can be displayed simultaneously (maximum of eight readings via selection keys)



SICON M multi control unit

The SICON M is externally identical to the SICON and offers the following additional options:

- Connect several devices
- Up to eight measuring channels can be operated via logical menu navigation

SICON – versatile combinable

Water

Drinking water treatment /
Waste water treatment



AquaScat S



ColorPlus 2 System



ColorPlus 3



ColorPlus 2

Beverages and food



TurBiScat



PhaseGuard



TurbiGuard

Industrial processes



ColorPlus 2

Traffic and environment



VisGuard 2



FireGuard 2

Details and
technical data:



SICON

Technical data

System data

Power supply:	9 .. 30 VDC
Power consumption:	5 W
Weight:	Ca. 0.6 kg
Protection degree:	IP 66
Material housing:	ABS
Dimensions:	160 x 157 x 60 mm

Display

Characteristics:	¼ VGA with touchscreen
Resolution:	320 x 240 pixels with 3.5" diagonal

Output

Analog: 4 x 0/4 .. 20 mA outputs, galvanically isolated up to max. 50 V to earth and max. 500 Ω load.

Digital: 7 x digital outputs up to max. 30 VDC, freely configurable, of which 1 output as relay normally closed.

Optional: With integrated 4-fold current output, four additional outputs (0/4 .. 20 mA, galvanically isolated up to max. 50 V to earth and max. 500 Ω load) are available.

Input

Analogue:	2x 0/4 .. 20mA analogue
Digital:	5 x digitale inputs up to max. 30 VDC, freely configurable.

Interface cards

Analogue / digital

Standard:

Ethernet, Modbus TCP, SD card (logging, SW update, diagnosis)

Optional:

Modules for Profibus DP, Modbus RTU, Profinet IO, HART and current output 4-fold, current input 4-fold