



Nennweite Nominal Size	Ø A	B	C	D
DN40	38	180	30	36
DN50	50	180	36	42
DN65	66	250	44	50
DN80	81	250	51.5	57.5
DN100	100	250	61	67
DN125	125	250	73.5	79.5
DN150	150	300	86	92
1 1/2" OD	34.9	180	28.5	34.5
2" OD	47.6	180	34.75	40.75
2 1/2" OD	60.3	250	41	47
3" OD	73	250	47.5	53.5
4" OD	97.4	250	59.75	65.75
2" IPS	56.3	228.6	39.5	45.5
3" IPS	84.3	304.8	53.5	59.5
4" IPS	109.7	304.8	66	72
6" IPS	162.7	304.8	92	98

Stecker 4-polig
plug 4-pole

1) Kühlwasseranschluss Ø 6 (optional)
cooling water connection Ø 6 (optional)

VARIVENT® In-line Gehäuse (optional)
VARIVENT® In-line access unit (optional)

Note: Content is for general information only and is subject to change without notification.

THIS DRAWING IS CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE MANUFACTURER AND MUST NOT BE COPIED OR LENT WITHOUT PERMISSION

Customer:
Project:
PO#
Reference:
Date:

Drawing: TurBiScat-MB REV: 01
Title: **TurBiScat**
Plan
DATE: 05/12/18 DWG BY: PRDCM

ProDetec
Measure . Prevent . Protect . Control

ProDetec Pty.Ltd.
P. +61 (02) 9620 8700
F. +61 (02) 9620 8755
E. info@prodetec.com.au
A. 17/38 Powers Rd,
Seven Hills NSW 2147
www.prodetec.com.au