

# Single Gas Clip Plus

**Hibernate mode allows it to rest when not in use extending the life of the detector**



- **Hibernate Mode - every minute rested is a minute of life saved**
- **Unmatched sensor reliability for H<sub>2</sub>S or CO**
- **Adjustable alarm set points & real-time gas reading capability**
- **0.1 ppm resolution for H<sub>2</sub>S sensor and display**
- **Two-way IR comms for event downloads, bump tests & updates**
- **Simple-to-use one-button operation**
- **“Bump Check” confirmation/identification**
- **No hidden service charges or maintenance fees**
- **Lightweight & durable - clamps on tight with alligator clip**

*Please note that the SGC Plus CO has been discontinued.*



Portable Gas Detectors You Can Count On

gascliptech.com • +1.972.775.7577 • Toll-free: 1.877.525.0808  
email: info@gascliptech.com

## Single Gas Clip Plus Versions

<b>Single Gas Clip Plus H<sub>2</sub>S</b> Part# SGC-P-H	Portable gas detector with Hibernate Mode for hydrogen sulfide (H <sub>2</sub> S)
<b>Single Gas Clip Plus CO</b> Part# SGC-P-C <i>(discontinued)</i>	Portable gas detector with Hibernate Mode for carbon monoxide (CO)

Included with detectors: calibration cap, calibration certificate & Quick Start Guide

## Single Gas Clip Accessories



### SGC Dock

Part# SGC-DOCK\*

Also available in High Pressure  
Part# SGC-DOCK-HP



### SGC Wall Mount Dock

Part# SGC-WMDOCK\*

Also available in High Pressure  
Part# SGC-WMDOCK-HP



### GCT IR Link

Part# GCT-IR-LINK



### SGC Manual Regulator

Part# SGC-REG



### 58L Gas Cylinders

H<sub>2</sub>S - 25 ppm H<sub>2</sub>S/N<sub>2</sub>  
Part# SGC-H2S-58

CO - 100 ppm CO/Air  
Part# SGC-CO-58



### 116L Gas Cylinders

H<sub>2</sub>S - 25 ppm H<sub>2</sub>S/N<sub>2</sub>  
Part# SGC-H2S-116

CO - 100 ppm CO/Air  
Part# SGC-CO-116

\*Detector(s) not included

Please contact Gas Clip Technologies for additional spare parts and accessories.

Distributed by:



ProDetec Pty.Ltd.  
 P. +61 (02) 9620 8700  
 F. +61 (02) 9620 8755  
 E. info@prodetec.com.au  
 A. 17/38 Powers Rd,  
 Seven Hills NSW 2147  
 www.prodetec.com.au

## SPECIFICATIONS

<b>Size - Weight</b>	3.4 H x 1.9 W x 1.1 D in. (85.5 x 48 x 29 mm.) • 2.7 oz. (76g)
<b>Temperature</b>	H <sub>2</sub> S: -40°F to +122°F (-40°C to +50°C) CO: -40°F to +122°F (-40°C to +50°C)
<b>Humidity</b>	5% to 95% RH (non-condensing)
<b>Battery Life</b>	Two Years
<b>Alarms</b>	Visual, vibrating & audible (minimum 95 dB) Detector life countdown (EOL), Low, High & Over limit (OL)
<b>Display</b>	High viewing angle Alphanumeric Liquid Crystal Display (LCD)
<b>Logs</b>	25 Events - newer events replace older events
<b>Tests</b>	Full function self-test upon activation and every 20 hours Continuous automatic battery tests
<b>Ratings</b>	EMC Directive 2004/108/EC      IP 67

### Certifications and Approvals



**CSA:** Intrinsically Safe/Sécurité Intrinsèque  
 Class I, Division 1, Groups A, B, C and D T4  
 EX ia IIC T4 Ga  
 Class I, Zone 0, AEx ia IIC T4 Ga  
 -40°C ≤ Ta ≤ +50°C (SGC-P-H, SGC-P-C)  
 CAN/CSA-C22.2 No. 60079-0:15  
 CAN/CSA-C22.2 No. 60079-11:14



**IECEx:** IECEx CSA 16.0020X  
 Ex ia IIC T4 Ga  
 -40°C ≤ Ta ≤ +50°C (SGC-P-H, SGC-P-C)  
 IEC 60079-0:2011 Edition: 6.0  
 IEC 60079-11:2011



**ATEX:** SIRA 16ATEX2087X  
 Ex ia IIC T4 Ga  
 -40°C ≤ Ta ≤ +50°C (SGC-P-H, SGC-P-C)  
 EN 60079-0:2012/A11:2013  
 EN 60079-11:2012

### Warranty

Three years from activation or 24 months of operational life, whichever occurs first

### Gases

H <sub>2</sub> S	Measuring range: 0-100 ppm Low alarm limit: 10 ppm - High alarm limit: 15 ppm
CO	Measuring range: 0-300 ppm Low alarm limit: 35 ppm - High alarm limit: 200 ppm

\*Note: Alarm set points listed above are factory default. These set points can be changed using the GCT IR Link (sold separately).

### Sensor Type

H<sub>2</sub>S & CO - Plug-in electrochemical cell

## USER OPTIONS



Custom user message	Display real-time gas readings or time remaining
Bump due LED	Self-test interval
Bump test interval	Low alarm set point
Calibration gas percentage	High alarm set point
Calibration interval	

Specifications are subject to change without notice due to ongoing product development.