

H8045N

LINEAR HEAT DETECTION (LHD)
(85°C, 185°F Nominal)



ProDetec

Measure . Prevent . Protect . Control

www.linesense.co.uk



General

The simple and proven technology of digital Linear Heat Detection (LHD) cable, makes it a product of choice for difficult and challenging applications where other technologies struggle to work.

With it's ease of installation and low maintenance it also provides a cost effective solution where project expenditure requires to be kept at a minimum.

The sensing cable is formed from a pair of twisted steel conductors each with temperature sensitive insulation and then an overall Nylon outer sleeve. When the temperature sensitive insulation reaches it's predetermined alarm temperature the two conductors short together providing the digital or switched signal.

The cable can be connected to any unit capable of monitoring a switched signal, i.e. Conventional fire panel, addressable switch monitor unit or PLC.

The nylon outer sleeve of the H8045N offers good chemical and water resistance, allowing it to be deployed in harsh and dirty environments.



ProDetec Pty.Ltd.

P. +61 (02) 9620 8700

F. +61 (02) 9620 8755

E. info@prodetec.com.au

A. 17/38 Powers Rd,

Seven Hills NSW 2147

www.prodetec.com.au

Features

Simple digital switch operation

Continuous sensing along the total length of the element.

Fixed alarm temperature. Unaffected by changes in ambient temperature.

Compatible with switch monitoring units and conventional alarm panels.

Suitable for use in Hazardous areas using safety barriers.

Chemical & water resistant

Rugged and durable construction.

Simple maintenance free installation.

Small diameter and bend radius.

FM Approved,

Applications

Conveyors / bearing protection

Escalators, moving walkways.

Petro-chemical storage tanks, rim seal protection

Cable tunnel / tray protection

Road and rail tunnels

Road and rail motor compartments

Electrical switch gear & transformers

Refrigerated rooms and cold stores.

Building exteriors under eaves

Motor and pump overheat detection.

Dirty and dusty environments.

H8045N

LINEAR HEAT DETECTION (LHD)
(85°C, 185°F Nominal)



Measure . Prevent . Protect . Control

www.linesense.co.uk

Specifications.

Alarm temperature :	85°C	185°F
Max amb temperature :	45°C	113°F
Min operating temperature :	-40°C	-47°F
Min installation temperature :	-15°C	5°F

Mechanical

Outside Diameter :	3.35mm
Colour :	Black.
Number of cores :	2
Core diameters :	0.9mm
Core colours:	Black and red.
Minimum bend radius :	50mm (Cold store 100mm)
Weight :	18Kg/Km on the reel. (weight of reel typically 2Kg)

Electrical

Resistance :	100 ohms / Km max @ 20°C
Capacitance :	45 pF/m to 130 pF/m
Inductance :	0.74 µH/m to 1.3 µH/m
Voltage rating :	110vdc 1amp

Time to detect small flame : 5 sec (Flame touching)

Approvals : FM 3210

Ordering Information

Part Number

51100-085

Description

H8045N sensing cable 85°C Alarm temperature
Black Nylon outer sleeve. (ordered by the meter)

Optional

52100-001

DLI-2K Digital Location Interface 2Km

52100-002

DLI-10K Digital Location Interface 10Km

52101-001

DIM Digital Interface Module DIN rail mounted.

53000-001

Portable test oven 1m