

LaserGas™ iQ² Vulcan



All Rights Reserved, Copyright © June 2018, NEO Monitors AS

NEO Monitors' LaserGas™ iQ² Vulcan is the first in-situ single-flange solution to measure up to four gases (O₂, CO, CH₄, H₂O) as well as the process temperature in a single unit. Based on the well-proven and trusted tunable diode laser absorption spectroscopy (TDLAS) technology, the solution combines cutting-edge design and ground-breaking functionality. It is a complete combustion solution eliminating the need for multiple units. Advanced TDLAS technology enables unmatched reliability and durability. Installation costs of this all-in-one solution are significantly reduced since only one flange is needed. In addition, operational and maintenance costs are kept at a minimum.

Features	Applications	Customer benefits
<ul style="list-style-type: none"> • No interference from background gases • Factory calibrated • No zero drift • Transceiver configuration • Automatic gain • In-situ measurement • Span check/validation option for O₂, CO, and CH₄ 	<ul style="list-style-type: none"> • Combustion analysis • Package boilers • Process heaters • Electrostatic precipitators • VCM waste gas recovery • Reformer gas 	<ul style="list-style-type: none"> • Up to 5 measuring components O₂, CO, CH₄, H₂O and temperature • Can handle a typical combustion process up to 1562 °F/850°C • Reduced installation cost • Low maintenance costs • Easy to install transceiver, one unit ensures easy alignment • Double path length increases absorption signal for low concentration • Well-proven technology

LaserGas™ iQ² Vulcan

Technical Data

<p>Specifications</p> <p>Max. process gas temperature: 850 °C</p> <p>Max. process gas pressure: 1.5 BarA</p> <p>Optical path length: 1 m</p> <p>Response time: 5 sec</p> <p>Environmental conditions</p> <p>Operating temperatures: -40 °C to +55 °C</p> <p>Storage temperature: -40 °C to +70 °C</p> <p>Protection classification: IP66</p> <p>Input/output</p> <p>Analog output(6): 4 - 20 mA current loop</p> <p>Digital output: Ethernet (TCP/IP)</p> <p>Relay output (6): High gas, warning and fault (normally closed)</p> <p>Analog input (2): 4 - 20 mA Process temperature and pressure reading</p>	<p>Ratings</p> <p>Power supply: 24 VDC (18 - 30 VDC)</p> <p>Power consumptions: max 30W</p> <p>4 - 20 mA: 500 Ohm max isolated</p> <p>Relay output: 1 A at 30 V DC/AC</p> <p>Safety</p> <p>Laser class: Class 1M according to IEC 60825-1, eye safe</p> <p>CE: Certified</p> <p>EMC: Conformant with directive 2014/30/EU</p> <p>Approvals</p> <p>IECEX/ATEX zone 1: II 2 G Ex pxb IIC T5 Gb II 2 D Ex pxb IIIC T100 °C Db</p> <p>CSA: Class I Div. 2</p> <p>Connection box:</p> <p>ATEX: II 2 GD Ex e IIC T5 Gb -40 °C ≤ Ta ≤ 65 °C</p>	<p>Installation and operation</p> <p>Flange dimension: DN80/PN 10-40 DN100/PN 10-40</p> <p>ANSI 3" #150/#300 ANSI 4" #150/#300</p> <p>Instrument purge: Nitrogen</p> <p>Probe purge: Nitrogen</p> <p>Calibration check: Every 12 months</p> <p>Dimensions / weight iQ²: 461 mm x 399 mm x 174 mm 15 kg</p> <p>Probe: 1495,8 mm x Ø 63,5 mm 32 kg</p>
---	---	--

Component	Max	LDL
CO	10000 ppm	3 ppm
O2	25 %	0.05 %
CH4 add-on	5 %	0.01 %
Process temperature	850 °C	
Process pressure	1.5 BarA	

NOTE: Detection limits are specified as the 95 % confidence interval for 1 m optical path and gas temperature / pressure = 25 °C / 1 BarA. Measured in N₂.

NEO Monitors reserves the right to change specifications without prior notice.

Your local distributor:



ProDetec Pty.Ltd.
P. +61 (02) 9620 8700
F. +61 (02) 9620 8755
E. info@prodetec.com.au
A. 17/38 Powers Rd,
Seven Hills NSW 2147
www.prodetec.com.au

